













































TFT (Thin-Film Transistor) Display Modules

No.	Diagonal	Display Format (HxV)	Picture	Model Name	Outline Dimensions (WxHxD)	Input Signal System	Ratio	Touch Screen Panel (USB/RS232)	LVDS KIT LVDS (20 Pins)		Open Frame (kein Modulerahmen)		Input Signal System
1	3.5"	320 x 234		LP035XLPS1-FDR	95.7 x 64.9 x 9.9	CVBS	4:3	-					
2	3.5"	640 x 480		LP035V2PB4-FDR	96.8 x 67 x 13.7	CVBS	4:3	4W Resistive	LT035V21A0-FDR				
3	4.3"	480 x 272		LP043A7IB4-FBR	118.5 x 69 x 21.65	CVBS	16:9	4W Resistive					
4	5"	640 x 480		LP050N2IB4-FBR	132.65 x 90.23 x 24.4	CVBS/ VGA	4:3	4W Resistive					
5	5.6"	640 x 480		LP056N5IB7-FBR	141.5 x 101.6 x 26.7	CVBS/ VGA	4:3	4W Resistive	LT056N51A0-FDR				
6	6.4"	320 x 234		LM06405PS0-FDR	156.3 x 119.8 x 16	CVBS	4:3	-					
7	6.4"	640 x 480		LP064P8B1-FBR	188.6 x 126.9 x 29.33	CVBS/ VGA	4:3	-					
8	6.5"	640 x 480		LP065GVAB4-FBR	166.6 x 119.73 x 28.95	CVBS	4:3	4W Resistive					
9	7"	800 x 480		LP070T8IB4-FBR	177.20 x 105.8 x 24.6	CVBS/ VGA	16:9	4W Resistive	LT070T81A0-FDR				
10	7"	1024 x 600		LP070A0654-FNR	180.5 x 107.19 x 23.25	HDMI	16:9	4W Resistive					
11	8"	800 x 600		LP080A1IB4-FBR	197.2 x 142.8 x 25.3	CVBS	4:3	4W Resistive	LT080A11A0-FDR				
12	8"	800 x 600		LP080S4PB4-FBR	197.2 x 142.8 x 24.5	CVBS/ VGA	4:3	4W Resistive					
13	10.4"	1024 x 768		LP104CWWB4-FBR	242 x 176.1 x 27	CVBS/ VGA	4:3	4W Resistive			LOF104D5A-KOOR		CVBS/ VGA
14	10.4"	1024 x 768		LP104X0114-FNR	244 x 176.1 x 28.6	HDMI/ CVBS/ VGA	4:3	4W Resistive			LOF104X13P-KOOR		VGA/ DVI/ HDMI
15	10.4"	800 x 600		LP104M2PB4-FBR	248.0 x 178.7 x 24.6	CVBS/ VGA	4:3	5W Resistive					
16	12.1"	1024 x 768		LP121L4EBV-FBR	276.7 x 205.8 x 28.3	CVBS/ VGA	4:3	5W Resistive			LOF12165A-KOOR		CVBS/ VGA
17	12.1"	1024 x 768		LP121X001U-FNR	290 x 205.6 x 31	VGA/ DVI/ HDMI	4:3	5W Resistive			LOF121X15P-OOR		VGA/ DVI/ HDMI
18	15"	1024 x 768		LP150L6IBV-FBR	346.7 x 255.3 x 34.55	CVBS/ VGA	4:3	5W Resistive			LOF150D5A-KOOR		CVBS/ VGA
19	15"	1024 x 768		LP150X501U-FNR	346.7 x 255.3 x 34.55	VGA/ DVI/ HDMI	4:3	5W Resistive			LOF150X35U-OOR LOF15003P-OOR		VGA/ DVI/ HDMI
20	15"	1024 x 768		LP150L5IBV-FBR	346.7 x 255.3 x 34.55	CVBS/ VGA	4:3	5W Resistive			LOF150X35P-OOR LOF15003U-OOR		VGA/ DVI/ HDMI
21	17"	1280 x 1024		LP170E021U-FNR	378.7 x 298.4 x 34.62	VGA / DVI / HDMI	4:3	5W Resistive			LOF170E23U-OOR/ LOF170E23P-OOR		VGA/ DVI/ HDMI

ARM Based TFT solution ARM Cortex-A8 @600MHz, Power VR SGX 530

No.	Diagonal	Display Format (H×V)	Picture	Model Name	Ratio	Base: Android 4.0 / WinCE6.0	Brightness	Touch Screen Panel (USB/RS232)	Starter Kit
1	5.6"	640 x 480		PK56Vx2AR2-00R	4:3	USB Port / Ethernet/WLAN/Storage Card/ Buzzer&Battery/ SkanKey&Audio (opt.)	350 cd/m ²	4W Resistive	X
2	6.5"	640 x 480		PK65Vx2AR2-00R	4:3	USB Port / Ethernet/WLAN/Storage Card/ Buzzer&Battery/ SkanKey&Audio (opt.)	800 cd/m ²	4W Resistive	
3	7"	800 x 480		PK70Wx1AR2-00R	16:9	USB Port / Ethernet/WLAN/Storage Card/ Buzzer&Battery/ SkanKey&Audio (opt.)	400 cd/m ²	4W Resistive	X
4	8"	800 × 600		PK80Sx1AR2-00R	4:3	USB Port / Ethernet/WLAN/Storage Card/ Buzzer&Battery/ SkanKey&Audio (opt.)	250 cd/m ²	4W Resistive	X
5	10.4"	800 × 600		PK44x1AR2-00R	4:3	USB Port / Ethernet/WLAN/Storage Card/ Buzzer&Battery/ SkanKey&Audio (opt.)	400 cd/m ²	4W Resistive	X

TFT (Thin-Film Transistor) GUI TFT Modules

No.	Diagonal	Display Format (H×V)	Picture	Model Name	Ratio	Outline Dimensions (W×H×D)	Power Consumption (Watts) (12V)	USP (Port)	Buzzer (Min.)	Battery	Touch Screen Panel (USB/RS232)	Starter Kit
1	3.5"	320×234		FG035QW00B-00R	4:3	88.9×65.7×14.5	1.98	USB (B Type)	85	Built-in(CR1220)	4W Resistive	X
2	4.3"	480x272		FG0431W001-00R	16:9	118.5x69x19.2	2.3	USB (A Type)	85	Built-in(CR1220)	4W Resistive	X
3	5.6"	640 x 480		FG0456VW001-00R	4:3	141.5x100.8x23.65	4.3	USB (A Type)	85	Built-in(CR1220)	4W Resistive	X
4	7"	800 x 480		FG070WW001-00R	16:9	177.2x105.8x21.4	4.3	USB (A Type)	85	Built-in(CR1220)	4W Resistive	X
5	8"	800 × 600		FG0804WW001-00R	4:3	197.2x142.8x22.3	4.25	USB (A Type)	85	Built-in(CR1220)	4W Resistive	X
6	10.4"	800 × 600		FG104BWW001-00R	4:3	248x178.7x21.6	6.3	USB (A Type)	85	Built-in(CR1220)	4W Resistive	X